


### DESCRIPTION:

TVS diodes can be used in a wide range of applications which like consumer electronic products, automotive industries, munitions, telecommunications, aerospace industries, and intelligent control systems.



SMC



Bi-directional



Uni-directional

Symbol

### FEATURES:

- ✧ Low profile package.
- ✧ Low inductance.
- ✧ Excellent clamping capability.
- ✧ 5000W peak pulse power capability at 10×1000μs waveform.
- ✧ Typical  $I_R$  less than 1μA above 30V.
- ✧ Fast response time: typically less than 1.0ps from 0V to  $V_{BR}$  min.
- ✧ High temperature to reflow soldering: 260°C/40s at terminals.
- ✧ Plastic package has under writers laboratory flammability 94V-0.
- ✧ Meets MSL level 1, per J-STD020, LF maximum peak of 260°C.
- ✧ For surface mounted applications in order to optimize board space.

8 "9 ) 4 ) ,

### ABSOLUTE MAXIMUM RATINGS ( $T_A=25^\circ\text{C}$ , RH=45%-75%, unless otherwise noted)

| Parameter                                                             | Symbol          | Value       | Unit |
|-----------------------------------------------------------------------|-----------------|-------------|------|
| Operating junction and storage temperature range                      | $T_J / T_{STG}$ | -55 to +150 | °C   |
| Steady state power dissipation at $T_L=75^\circ\text{C}$              | $P_{M(AV)}$     | 6.5         | W    |
| Peak pulse power dissipation on 10/1000μs waveform                    | $P_{PP}$        | 5000        | W    |
| Maximum instantaneous forward voltage at 100A for unidirectional only | $V_F$           | 5.0         | V    |
| Peak forward surge current, 8.3ms single half sine wave(Note 1)       | $I_{FSM}$       | 300         | A    |
| Typical thermal resistance junction to lead                           | $R_{\theta JL}$ | 15          | °C/W |
| Typical thermal resistance junction to ambient                        | $R_{\theta JA}$ | 75          | °C/W |

### Notes:

1. Measured on 8.3ms single half sine wave or equivalent square wave for unidirectional device only, duty cycle=4 per minute maximum

### ELECTRICAL CHARACTERISTICS (T<sub>A</sub>=25°C)

| PART NUMBER   |              | REVERSE STAND-OFF VOLTAGE | BREAKDOWN VOLTAGE VBR(V)MAX.@IT |            | TEST CURRENT | REVERSE LEAKAGE @VRWM | PEAK PULSE CURRENT | MAXIMUM CLAMPING VOLTAGE @Ipp |
|---------------|--------------|---------------------------|---------------------------------|------------|--------------|-----------------------|--------------------|-------------------------------|
| BI-POLAR      | UNI-POLAR    | VRWM (V)                  | VBR MIN(V)                      | VBR MAX(V) | IT (mA)      | IR (μA)               | Ipp (A)            | Vc (V)                        |
| 5.0SMDJ5.0CA  | 5.0SMDJ5.0A  | 5.0                       | 6.4                             | 7.25       | 50           | 5000                  | 554.3              | 9.2                           |
| 5.0SMDJ6.0CA  | 5.0SMDJ6.0A  | 6.0                       | 6.67                            | 7.67       | 50           | 5000                  | 495.1              | 10.3                          |
| 5.0SMDJ 6.5CA | 5.0SMDJ 6.5A | 6.5                       | 7.22                            | 8.30       | 50           | 2000                  | 455.4              | 11.2                          |
| 5.0SMDJ7.0 CA | 5.0SMDJ7.0 A | 7.0                       | 7.78                            | 8.95       | 50           | 1000                  | 425.0              | 12.0                          |
| 5.0SMDJ 7.5CA | 5.0SMDJ 7.5A | 7.5                       | 8.33                            | 9.58       | 10           | 250                   | 395.3              | 12.9                          |
| 5.0SMDJ 8.0CA | 5.0SMDJ 8.0A | 8.0                       | 8.89                            | 10.23      | 10           | 150                   | 357.0              | 13.6                          |
| 5.0SMDJ8.5 CA | 5.0SMDJ8.5 A | 8.5                       | 9.44                            | 10.82      | 10           | 50                    | 354.2              | 14.4                          |
| 5.0SMDJ9.0 CA | 5.0SMDJ9.0 A | 9.0                       | 10.00                           | 11.50      | 10           | 20                    | 331.2              | 15.4                          |
| 5.0SMDJ10CA   | 5.0SMDJ10A   | 10.0                      | 11.1                            | 12.30      | 10           | 15                    | 300.0              | 17.0                          |
| 5.0SMDJ11CA   | 5.0SMDJ11A   | 11.0                      | 12.20                           | 14.00      | 10           | 2                     | 280.2              | 18.2                          |
| 5.0SMDJ12CA   | 5.0SMDJ12A   | 12.0                      | 13.30                           | 14.70      | 10           | 2                     | 256.3              | 19.9                          |
| 5.0SMDJ13CA   | 5.0SMDJ13A   | 13.0                      | 14.40                           | 16.50      | 10           | 2                     | 237.2              | 21.5                          |
| 5.0SMDJ14CA   | 5.0SMDJ14A   | 14.0                      | 15.60                           | 17.20      | 10           | 2                     | 219.8              | 23.2                          |
| 5.0SMDJ15CA   | 5.0SMDJ15A   | 15.0                      | 16.70                           | 19.20      | 1            | 2                     | 209.0              | 24.4                          |
| 5.0SMDJ16CA   | 5.0SMDJ16A   | 16.0                      | 17.80                           | 19.70      | 1            | 2                     | 196.2              | 26.0                          |
| 5.0SMDJ17CA   | 5.0SMDJ17A   | 17.0                      | 18.90                           | 21.70      | 1            | 2                     | 184.8              | 27.6                          |
| 5.0SMDJ18CA   | 5.0SMDJ18A   | 18.0                      | 20.00                           | 23.30      | 1            | 2                     | 174.7              | 29.2                          |
| 5.0SMDJ20CA   | 5.0SMDJ20A   | 20.0                      | 22.20                           | 25.50      | 1            | 2                     | 157.4              | 32.4                          |
| 5.0SMDJ22CA   | 5.0SMDJ22A   | 22.0                      | 24.40                           | 28.00      | 1            | 2                     | 143.7              | 35.5                          |
| 5.0SMDJ24CA   | 5.0SMDJ24A   | 24.0                      | 26.70                           | 30.70      | 1            | 2                     | 131.1              | 38.9                          |
| 5.0SMDJ26CA   | 5.0SMDJ26A   | 26.0                      | 28.90                           | 33.20      | 1            | 2                     | 121.1              | 42.1                          |
| 5.0SMDJ28CA   | 5.0SMDJ28A   | 28.0                      | 31.10                           | 35.80      | 1            | 2                     | 112.3              | 45.4                          |
| 5.0SMDJ30CA   | 5.0SMDJ30A   | 30.0                      | 33.30                           | 38.30      | 1            | 2                     | 105.4              | 48.4                          |
| 5.0SMDJ33CA   | 5.0SMDJ33A   | 33.0                      | 36.70                           | 40.60      | 1            | 2                     | 95.7               | 53.3                          |



① Surge waveform: 10/1000 $\mu$ s


$V_R$ : Stand-off voltage -- Maximum voltage that can be applied

$V_{BR}$ : Breakdown voltage

$V_C$ : Clamping voltage -- Peak voltage measured across the suppressor at a specified  $I_{PP}$


$I_R$ : Reverse leakage current

## ORDERING INFORMATION




## RATINGS AND V-I CHARACTERISTICS CURVES ( $T_A=25^\circ\text{C}$ , unless otherwise noted)


**FIG.1: V- I curve characteristics (Uni-directional)**




**FIG.2: V- I curve characteristics (Bi-directional)**



**FIG.3: Pulse waveform**




**FIG.4: Pulse derating curve**




### SOLDERING PARAMETERS

|                                                        |                                   |                                 |
|--------------------------------------------------------|-----------------------------------|---------------------------------|
| Reflow Condition                                       |                                   | Pb-Free assembly<br>(see FIG.5) |
| Pre Heat                                               | -Temperature Min ( $T_{s(min)}$ ) | +150°C                          |
|                                                        | -Temperature Max( $T_{s(max)}$ )  | +200°C                          |
|                                                        | -Time (Min to Max) (ts)           | 60-180 secs.                    |
| Average ramp up rate (Liquidus Temp ( $T_L$ ) to peak) |                                   | 3°C/sec. Max                    |
| $T_{s(max)}$ to $T_L$ - Ramp-up Rate                   |                                   | 3°C/sec. Max                    |
| Reflow                                                 | -Temperature( $T_L$ )(Liquidus)   | +217°C                          |
|                                                        | -Temperature( $t_L$ )             | 60-150 secs.                    |
| Peak Temp ( $T_p$ )                                    |                                   | +260(+0/-5)°C                   |
| Time within 5°C of actual Peak Temp ( $t_p$ )          |                                   | 20-40secs.                      |
| Ramp-down Rate                                         |                                   | 6°C/sec. Max                    |
| Time 25°C to Peak Temp ( $T_p$ )                       |                                   | 8 min. Max                      |
| Do not exceed                                          |                                   | +260°C                          |




### PACKAGE MECHANICAL DATA



| Ref. | Dimensions  |       |        |       |
|------|-------------|-------|--------|-------|
|      | Millimeters |       | Inches |       |
|      | Min.        | Max.  | Min.   | Max.  |
| A    | 5.75        | 6.25  | 0.226  | 0.246 |
| B    | 6.90        | 7.40  | 0.272  | 0.291 |
| C    | 2.75        | 3.25  | 0.108  | 0.128 |
| D    | 0.95        | 1.52  | 0.037  | 0.060 |
| E    | 7.70        | 8.20  | 0.303  | 0.323 |
| F    | 0.051       | 0.203 | 0.002  | 0.008 |
| G    | 0.15        | 0.31  | 0.006  | 0.012 |
| H    | 2.15        | 2.62  | 0.085  | 0.103 |
| J    | 2.40        |       | 0.094  |       |
| K    |             | 4.20  |        | 0.165 |
| L    | 3.30        |       | 0.130  |       |

### TAPE AND REEL SPECIFICATION-SMC



| Ref. | Dimensions  |                |
|------|-------------|----------------|
|      | Millimeters | Inches         |
| A0   | 6.05 ± 0.3  | 0.238 ± 0.012  |
| B0   | 8.31 ± 0.3  | 0.327 ± 0.012  |
| C    | 330.0       | 13.0           |
| D0   | 1.55 ± 0.1  | 0.061 ± 0.004  |
| E    | 1.75 ± 0.2  | 0.069 ± 0.008  |
| E1   | 13.3 ± 0.3  | 0.524 ± 0.012  |
| F    | 7.50 ± 0.2  | 0.295 ± 0.008  |
| P0   | 4.00 ± 0.2  | 0.157 ± 0.008  |
| P1   | 8.00 ± 0.2  | 0.3145 ± 0.008 |
| P2   | 2.00 ± 0.2  | 0.079 ± 0.008  |
| W    | 16.0 ± 0.2  | 0.630 ± 0.008  |
| W1   | 19.7 ± 2.0  | 0.776 ± 0.079  |

| PART No.      | UNIT WEIGHT<br>(g/PCS) typ. | REEL<br>(PCS) |
|---------------|-----------------------------|---------------|
| 5.0SMDJxxCA/A | 0.294/0.342<br>(NOTE)       | 3,000         |

**Notes:** 0.342g/PCS for single die; 0.294g/PCS for stacked dies

\$ I \$ 5 >  
 H&% - & . . . & %  
 / 7 H &% - & ( @ @ & - <